



Lether Gewerbestraße 10
Großenkneten 26197

Phone: +49 (0)4435 9735500
Fax: +49 (0)4435 916908

Intelligent solutions for your energy concept Our qualified team engages in the process of searching for feasible ways to meet your needs. We supply quality as per ISO 9001 and CE standards, always guaranteeing the optimal price/performance ratio to you. Our goal is to sustainably satisfy the demands of our customers by finding intelligent solutions for their energy and drive system projects. Electric motors Electric motors from a specialist contractor JS-Technik GmbH is one of the leading suppliers on the electric motors online market in Germany. Our focus is on three-phase motors, frequency inverters and geared motors. You can also visit us via our subdomains elektromotor.co. Cast iron electric motors Aluminum electric motors IP23 - Electric motors Stainless steel - electric motors Single phase motors Pole-changing motors Brake motors ATEX Motors Circular saw motors Flat motors / Saw motors Medium voltage motors DC motors Geared motors Extensive selection of geared motors Our range of products includes worm gear motors, spur gear motors, flat gear motors, planetary gear sets, bevel gearboxes and many more. We're offering you drive systems of the highest quality. They stand out due to their high power and a long serviceable life. Moreover, they produce little noise, are subjected to little wear and are available in ATEX design.

Worm gearbox with motor Worm gearbox without motor Helical geared motors M-Series Helical bevel gear motors K-Series Parallel shaft geared motors D-Series Planetary geared motors P-Series Heavy duty gears - H series Stainless steel - Worm gear motors Stainless steel - Helical gear motors Stainless steel - Bevel gear motors Direct current - Worm gear motors Direct current - Helical geared motors Direct current - Helical bevel gear motors Direct current - Parallel shaft geared motors Frequency inverter Low-priced frequency inverters for your individual application JS-Technik GmbH is specialized on a wide range of challenges in the professional drive technology field with a focus on electric motors, frequency inverters and geared motors. The primary function of a frequency converter in aquatic applications is to provide energy savings. By controlling speed of a pump rather than controlling flow through use of throttling valves, energy savings can be substantial. By way of example, a speed reduction of 20% can yield energy savings of 50%. The following describes speed reduction and corresponding energy savings. In addition to energy savings, impeller, bearing and seal life is greatly improved.

LS-M100 - Frequency inverter LS-G100 - Frequency inverter LS-S100 - Frequency inverter LS-H100 - Frequency inverter LS-iS7 - Frequency inverter EASYdrive - Frequency inverter with motor EASYdrive Frequency inverter SMARTdrive - Frequency inverter with motor SMARTdrive Frequency inverter Soft Starters DC-Motor Control Geared motors with speed control Geared motors with integrated control unit Our general range of geared motors includes controllable drives. Thus, a variable-speed adjustment unit can be integrated with several gearbox sizes. We offer this with an integrated adjusting gear, which is mounted between the electric motor and the actual gearbox and is to be controlled by a handwheel. Furthermore, we offer the version with a frequency converter, which is mounted directly on the electric motor. The speed control can be done via the potentiometer or via the PC. These options apply to our complete gear range, i.e. for worm geared motors,

helical geared motors, geared motors, planetary geared motors and bevel geared motors. You order and buy drives of the highest quality from us. They are characterized by high performance and long life / durability. Worm gear motor with handwheel speed control Worm gear motor with integrated frequency inverter Spur gear motor with handwheel speed control Spur gear motor with integrated frequency inverter Accessories electric motors External fan Brakes Encoders Shaft couplings Motor protection switch Cylindrical roller bearings, flanges, etc. Rain protection Motorized clamping slide Motor slide rails Engine switch Cam switch Cables and glands Accessories geared motors Worm Gear CMRV-Series Helical gear M-Series Bevel gear K-Series Parallel shaft gear D-Series Stainless steel gears Accessories - Frequency inverter Frequency inverter accessories JS-Technik GmbH specializes in comprehensive challenges in the field of professional drive technology with a focus on frequency converters, three-phase motors and gear motors. Of course, we also offer you the necessary accessories. These also include potentiometers, remote cables, mounting adapters, connection cables, external control panels, mains chokes, Modbus interface cards, manual control units, Profibus interface cards, right / left switch with emergency stop in the housing and 0-10V foot switch. Control panels / cables Braking resistors EMC filter frequency inverter Switches / Regulators Connection and control cables Interface cards Special and remaining items Three-phase motors - aluminum Three-phase motors - cast iron Brake motors Flachmotoren / Sägemotoren Worm gear motors Spur gear motors Frequency inverter Accessories - General JS-Technik motors are...

- three-phase asynchronous squirrel cage motors, completely enclosed, fan-cooled (TEFC).
- JS-Technik motors of the grey cast series are available in sizes 80 - 400 with 2, 4, 6, 10 and 12 poles; various combinations of two-pole or n-pole design ($n \geq 2$), in sizes 160 to 315. The position of the terminal box is typically on the right. Terminal box on the left

or at the top can be supplied on request.

- JS-Technik also offers three-phase asynchronous squirrel cage motors in aluminium design, completely enclosed, fan-cooled (TEFC). The JS-Technik motors are available in sizes 56 - 132 with 2, 4, 6 and 8 poles.

The position of the terminal box is typically at the top. On request, motor sizes 63 - 132 can be supplied with the terminal box on the left or right.

- All JS-Technik motors are manufactured in accordance with IEC 34 - 1/9, IEC 85, DIN 57530 / VDE 0530-1291.

- Every JS-Technik motor in the size range of 160 - 400 mm has a grey-cast iron sheet on the drive side and on the opposite side.

- Class of protection: IP55, as per IEC 35-5 / DIN VDE 0530 Part 5

- Class of isolation: F

- Temperature increase: class F

- Colour of the surface finish: gentian blue (RAL 5010)

- Paint: primer paint (layer of approx. 30 µm) and surface finish paint for general industrial applications (layer of approx. 45 - 90 µm), climate zone worldwide as per EN721-2-1.

[Visit Website](#)

[Send Message](#)

[Email Friend](#)