



Hauptstr. 59
Appen 25482

Phone: +49 (0)4101 22763
Fax: +49 (0)4101 204208

A program with over 8000 different bearing springs according to DIN and ISO. Usually dispatched directly from the warehouse within 24 hours using a parcel service. Bearing springs save you design time, delivery time and money. We also deliver custom-made products according to your wishes.

Products
Compression springs
Tension springs
Feather portfolios
Spring wires
ISO tool springs
Stamp nibs
RaymondDisc springs
Spring washers
Support and shims
Jagged rings
Circlips
Snap rings
shaft
Spring steel clips
Compression springs hoses
Tension springs hoses
To calculate the force at a specific spring length, the spring rate (N/mm) must be multiplied by the spring travel (in mm). To theoretically calculate the block height (L_c) of the ground compression spring, the wire diameter (d) must be multiplied by the total number of turns ($n_t = n + 2$). For unground compression springs, the total number of turns results from the free turns +3 ($n_t = n + 3$) and must be multiplied by the wire thickness (d) to calculate the block height (L_c). For stainless material, $F_n = 0.833 \times F_n$ is calculated from spring steel wire grade C. If springs with a higher spring rate (R) are required, please use tool springs. Prices are

subject to change and apply ex works. If the cost situation changes, we reserve the right to adjust the price. The current price list on the Internet applies.

[Visit Website](#)

[Send Message](#)

[Email Friend](#)